



B Y R I C H A R D W E R N E K I N C K

Hugo de Grootstraat 175, 2613 VS Delft, NL
T +31 15 214 63 41 | F + 31 15 213 20 04
sales@hollandfelt.nl | www.hollandfelt.nl

GENERAL INFORMATION

Woolfelt made of Pure New Wool in 1,2,3,4 and 5 mm thick and 90 colours on rolls with a width of 183cm and a length of +/- 20m. We do not have a minimum order quantity and almost everything is always in stock.

TECHNICAL DATA

- PURE NEW WOOL conform "international wool secretariat"
- NON TOXIC conform Öko-Tex Test no. 990585
- Made in EC
- NON-FLAMMABLE conform UNE 23735 Class M1, NEN-EN-13501 Class B1
- SOUND ABSORPTION according to UNE-EN ISO 354:2004 up to 0,82 s (5mm) and 0,56 s (3mm)
- MARTINDALE TEST 15000 CONFORM UNE-EN-ISO 12947/14465
- PILLING RESISTANCE Degree 3 conform UNE-EN-ISO 12945-2-2001
- TEAR RESISTANCE conform UNE-EN-ISO 13936-2 in length 2,3 in width 1,8
- CHANGE in dry cleaning in length -1,0% in width 0,0%
- CHANGE in hand wash (first time) in length max. -8,0% in width max. -9,5%
- 100% RECYCLABLE

MAINTENANCE

- dry stains and dust → vacuum occasionally
- wet spills → directly blot with dry cloth or paper towel. If necessary, rinse with cold water and blot again until dry
- grease stains → clean with K2r
- Iron lukewarm

ADDITIONAL TREATMENTS ON REQUEST

With a minimum order of 20m we can add one of the treatments listed below

- Your own colour
- Anti-moth
- Extra dirt repellent
- Extra colour fast
- Shrink free

CUSTOM MADE

We can (laser)cut or punch our Woolfelt in every shape and dimension. We can inform you about the possibilities and advise you about the application of the felt in your project.

WOOLFELT
WALLCOVERING

- eco-friendly
- nonflammable
- enhances acoustics