



HOLLANDFELT®

BY RICHARD WERNEKINCK

Woolfelt from HOLLANDFELT

Woolfelt is an immemorial and sustainable material that can be applied in many ways. Our Woolfelt is made of Pure New Merino Wool, mainly from Australia. The wool is washed, carded, felted and dyed in different factories around Western Europe before it reaches our warehouse in Delft.

ENHANCES ACOUSTICS

Woolfelt has the quality to enhance acoustics in spaces and therefore is a prime solution for your wall, floor or ceiling. Furthermore it is 100% recyclable. For use on ceilings and walls we recommend Woolfelt of at least 3mm thickness. For floors we have a special carpet quality Woolfelt which has been felted twice and is therefore more durable. It is possible that your situation requires thicker Woolfelt than the 5mm we have in stock. Contact us for the possibilities.

As wall covering Woolfelt now can be glued directly onto the wall. First the glue is applied on the wall, then the felt is pressed into the glue. Eurocol has developed glues especially for this purpose.

REGULATES CLIMATE AND LIGHT

For curtains we recommend 2mm thick Woolfelt. This is thick enough to regulate light, cold and heat and the pleats are more beautiful with 2mm thickness than with 1mm thickness.

ENSURES A SUSTAINABLE SURFACE

For soft furnishing 1mm thick Woolfelt is used. In case of very high demands on durability 2mm thick Woolfelt can also be used.

IS SAFE FOR USE IN PUBLIC SPACES

Because of the natural characteristics of Woolfelt (inflammable, insulating, dirt and water repellent) it is suitable for use in catering, hospitals, theatres and museums. The material does not need impregnation



HOLLANDFELT Technical information

Woolfelt made of Pure New Wool in 1,2,3,4 and 5 mm thick and 90 colours on rolls with a width of 183cm and a length of +/- 20m. We do not have a minimum order quantity and almost everything is always in stock.

TECHNICAL DATA

- PURE NEW WOOL conform "international wool secretariat"
- NON TOXIC conform Öko-Tex Test no. 990585
- Made in EC
- INFLAMMABLE conform UNE 23735 Class M1, NEN-EN-13501 Class A1
- SOUND ABSORPTION according to UNE-EN ISO 354:2004 up to 0,82 α s (5mm) and 0,56 α s (3mm)
- MARTINDALE TEST 15000 CONFORM UNE-EN-ISO 12947/14465
- PILLING RESISTANCE Degree 3 conform UNE-EN-ISO 12945-2-2001
- TEAR RESISTANCE conform UNE-EN-ISO 13936-2 in length 2,3 in width 1,8
- CHANGE in dry cleaning in length -1,0% in width 0,0%
- CHANGE in hand wash (first time) in length max. -8,0% in width max. -9,5%
- 100% RECYCLABLE

MAINTENANCE

- Vacuum
- Chemical cleaning / hand wash
- Iron lukewarm

ADDITIONAL TREATMENTS ON REQUEST

With a minimum order of 20m we can add one of the treatments listed below

- Anti-moth
- Extra dirt repellent
- Extra colour fast
- Shrink free
- Your own colour

CUSTOM MADE

We can (laser)cut or punch our Woolfelt in every shape and dimension. We can inform you about the possibilities and advise you about the application of the felt in your project.